# **SK** functional polymer

### **SAFETY DATA SHEET**

### **EVATANE® 28-03**

### 1. PRODUCT AND COMPANY IDENTIFICATION

### **Company**

SK Global Chemical Americas 501 Office Center Drive, Suite 188 Fort Washington, Pennsylvania 19034

**Specialty Polyamides** 

Customer Service Telephone Number: (267) 896-3500

(Monday through Friday, 8:00 AM to 5:00 PM EST)

**Emergency Information** 

Transportation: CHEMTREC: (800) 424-9300

(24 hrs., 7 days a week)

Medical: Rocky Mountain Poison Center: (866) 767-5089

(24 hrs., 7 days a week)

**Product Information** 

Product name: EVATANE® 28-03

Synonyms: UBa4

Molecular formula: Not applicable

**Chemical family:** Ethylene and vinyl acetate copolymer **Product use:** Adhesives, Films, Extrusion - blow moulding

### 2. HAZARDS IDENTIFICATION

**Emergency Overview** 

Color: white
Physical state: solid
Form: pellets
Odor: ester-like

### \*Classification of the substance or mixture:

Not a hazardous substance or mixture.

### **GHS-Labelling**

### **Supplemental Hazard Statements:**

Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

### Supplemental information:

### **Potential Health Effects:**

The product, in the form supplied, is not anticipated to produce significant adverse human health effects upon acute exposure. Contains high molecular weight polymer(s). Effects due to processing releases or residual monomer: Irritating to eyes, respiratory system and skin.

Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects



### **EVATANE® 28-03**

depends on extent of exposure).

### Other:

Handle in accordance with good industrial hygiene and safety practice. (pellets/granules) This product may release fume and/or vapor of variable composition depending on processing time and temperature. Hazardous decomposition products may include confirmed or suspected carcinogens.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                                  | CAS-No.    | Wt/Wt   | GHS Classification**            |
|--|------------|---------|---------------------------------|
| Acetic acid ethenyl ester, polymer with ethene | 24937-78-8 | >= 99 % | Not classified                  |
| Acetic acid ethenyl ester                      | 108-05-4   | < 0.5 % | H332, H335, H225, H351,<br>H411 |

<sup>\*\*</sup>For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

### 4.1. Description of necessary first-aid measures:

### Inhalation:

If inhaled, remove victim to fresh air.

### Skin:

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

### Eves:

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

### Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms/effects, acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary:



### **EVATANE® 28-03**

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

### **5. FIREFIGHTING MEASURES**

### Extinguishing media (suitable):

Water spray, Carbon dioxide (CO2), Foam, Dry chemical

### **Protective equipment:**

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

### Further firefighting advice:

Fire fighting equipment should be thoroughly decontaminated after use.

### Fire and explosion hazards:

When burned, the following hazardous products of combustion can occur: Carbon oxides
Hazardous organic compounds
Acetic acid

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:

Prevent further leakage or spillage if you can do so without risk. Ventilate the area. Sweep up and shovel into suitable properly labeled containers for prompt disposal. Possible fall hazard – floor may become slippery from leakage/spillage of product. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

### **Protective equipment:**

Appropriate personal protective equipment is set forth in Section 8.

### 7. HANDLING AND STORAGE

### **Handling**

### General information on handling:

Avoid breathing dust.

Avoid breathing processing fumes or vapors.

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

### **Storage**

### General information on storage conditions:

Store in closed containers, in a secure area to prevent container damage and subsequent spillage.

### Storage stability – Remarks:



### **EVATANE® 28-03**

Stable under normal conditions.

### Storage incompatibility - General:

None known.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Airborne Exposure Guidelines:**

### Acetic acid ethenyl ester (108-05-4)

US. ACGIH Threshold Limit Values

Time weighted average 10 ppm Short Term Exposure Limit (STEL): 15 ppm

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

### **Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

### Respiratory protection:

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

### Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

### Eye protection:

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

| 9. PHYSICAL AND CHEMICAL PROPERTIES |       |  |
|-------------------------------------|-------|--|
| Color:                              | white |  |



### SAFETY DATA SHEET EVATANE® 28-03

Physical state: solid

Form: pellets

Odor: ester-like

Odor threshold: No data available

Flash point Not applicable

Auto-ignition temperature:

n No data available

Lower flammable limit

(LFL):

No data available

Upper flammable limit

(UFL):

No data available

pH: Not applicable

**Density:** 0.95 g/cm3

Vapor pressure: Not applicable

Vapor density: Not applicable

**Boiling point/boiling** 

range:

No data available

Melting point/range: 169 °F (76 °C)

Freezing point: No data available

**Evaporation rate:** No data available

**Solubility in water:** 68 °F (20 °C) insoluble (on the basis of its structure)

Solubility in other

solvents: [qualitative and

quantative]

77 °F (25 °C) Soluble in: Carbon tetrachloride

Viscosity, dynamic: No data available

Oil/water partition

coefficient:

No data available

Thermal decomposition approx. 500 °F (260 °C)

Flammability: See GHS Classification in Section 2



## SAFETY DATA SHEET EVATANE® 28-03

### 10. STABILITY AND REACTIVITY

### Stability:

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

### Hazardous reactions:

Hazardous polymerization does not occur.

#### Materials to avoid:

None known.

#### Conditions / hazards to avoid:

Avoid storing in moist and warm conditions. (to maintain the technical properties of the product). See Hazardous Decomposition Products below.

### Hazardous decomposition products:

Thermal decomposition giving toxic, flammable, and / or corrosive products: Carbon oxides
Hazardous organic compounds
Acetic acid

### 11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

### Data for Acetic acid ethenyl ester, polymer with ethene (24937-78-8)

### **Acute toxicity**

### Oral:

May be harmful if swallowed. (rat) LD50 > 2,500 mg/kg.

### **Other information**

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance.

### Data for Acetic acid ethenyl ester (108-05-4)

### **Carcinogenicity**

Long term inhalation administration to rat / affected organ(s): lung, upper respiratory tract / signs: Increased incidence of tumors was reported.

Long term drinking water administration to rat and mouse / affected organ(s): Gastro-intestinal tract / signs: Increased incidence of tumors was reported.

Classified by the International Agency for Research on Cancer as: Group 2B: Possibly carcinogenic to humans.

### Genotoxicity



## SAFETY DATA SHEET EVATANE® 28-03

### Assessment in Vitro:

Both positive and negative responses for genetic changes were observed in laboratory tests using: animal cells

No genetic changes were observed in laboratory tests using: bacteria

### Genotoxicity

### Assessment in Vivo:

Both positive and negative responses for genetic changes were observed in laboratory tests using: rats, mice

### Human experience

#### Inhalation:

Upper respiratory tract: irritation. (based on reports of occupational exposure to workers) (extent of injury depends on severity of exposure)

Eyes: irritation. (based on reports of occupational exposure to workers) (extent of injury depends on severity of exposure)

### 12. ECOLOGICAL INFORMATION

### **Chemical Fate and Pathway**

No data are available.

### **Ecotoxicology**

No data are available.

### 13. DISPOSAL CONSIDERATIONS

### Waste disposal:

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

### 14. TRANSPORT INFORMATION

US Department of Transportation (DOT): not regulated

International Maritime Dangerous Goods Code (IMDG): not regulated



### **EVATANE® 28-03**

### 15. REGULATORY INFORMATION

**Chemical Inventory Status** 

EU. EINECS EINECS Conforms to

US. Toxic Substances Control Act

TSCA

The components of this product are all on

the TSCA Inventory.

Australia. Industrial Chemical (Notification and AICS Conforms to

Assessment) Act

Canada. Canadian Environmental Protection Act DSL All components of this product are on the

Canadian DSL

Japan. Kashin-Hou Law List ENCS (JP) Conforms to

Korea. Existing Chemicals Inventory (KECI) KECI (KR) Conforms to

Philippines. The Toxic Substances and Hazardous PICCS (PH) Conforms to

and Nuclear Waste Control Act

(CEPA). Domestic Substances List (DSL)

China. Inventory of Existing Chemical Substances IECSC (CN) Conforms to

**United States - Federal Regulations** 

SARA Title III - Section 302 Extremely Hazardous Chemicals:

Chemical name CAS-No. SARA SARA

Reportable Threshold
Quantities Planning
Quantity

Acetic acid ethenyl ester 108-05-4 5000 lbs 1000 lbs

SARA Title III - Section 311/312 Hazard Categories:

No SARA Hazards

SARA Title III - Section 313 Toxic Chemicals:

The following components are subject to reporting levels established by SARA Title III, Section 313:

Chemical name CAS-No. De minimis Reportable threshold:

Acetic acid ethenyl ester 108-05-4 0.1 % 10000 lbs (Otherwise used

concentration

(non-

manufacturing/processing)) 25000 lbs (Manufacturing

and processing)



### **EVATANE® 28-03**

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

<u>Chemical name</u> <u>CAS-No.</u> <u>Reportable quantity</u>

Acetic acid ethenyl ester 108-05-4 5000 lbs

### **United States - State Regulations**

### **New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

### Pennsylvania Right to Know

<u>Chemical name</u> <u>CAS-No.</u>
Acetic acid ethenyl ester, polymer with ethene 24937-78-8

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

### 16. OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

### Latest Revision(s):

Revised Section(s): Chapter 4 update
Reference number: 000000027259
Date of Revision: 05/06/2016
Date Printed: 07/23/2016

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, SKGCA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.